

CHICAGO, MILWAUKEE, ST. PAUL
AND PACIFIC RAILROAD CO.

HASTINGS & DAKOTA
DIVISION

TABLE OF TRAIN SPEEDS			
Seconds per Mile	Miles per Hour	Seconds per Mile	Miles per Hour
36	100	59	61
37.9	95	60	60
40	90	61	59
42.4	85	62	58.1
45	80	63	57.1
46	78.3	64	56.3
47	76.6	65	55.4
48	75	66	54.5
49	73.5	67	53.7
50	72	68	52.9
51	70.6	69	52.2
52	69.2	70	51.4
53	67.9	75	48
54	66.7	80	45
55	65.5	85	42.4
56	64.3	90	40
57	63.2	100	36
58	62.1	120	30

TIME
TABLE
No. 17

Taking effect at 12:01 A. M.
Central Standard Time

Sunday, September 30, 1951

For the government and information
of employes only

J. W. WOLF,
Assistant Superintendent.

K. R. SCHWARTZ,
Superintendent.

C. H. WINTERS,
General Superintendent of Transportation.

J. J. O'TOOLE,
Assistant General Manager.

W. J. WHALEN,
General Manager.

FIRST SUBDIVISION—WESTWARD

TIME TABLE NO. 17 September 30, 1951 STATIONS	Distance from Minneapolis.	Telegraph calls	Capacity in cars. Siding Other tracks	FIRST CLASS			SECOND CLASS			THIRD CLASS	
				17	5	15	263	63		91	
				Passenger Daily	Passenger Daily	Passenger Daily	Time Freight Daily	Time Freight Daily		Way Freight Daily Except Sun.	
MINNEAPOLIS 1.9		C		L 7.55 AM	L 8.30 PM	L 10.25 PM					
SOUTH MINNEAPOLIS 4.6	1.9	ON		Yard 8.18	8.38	10.48	L 11.00 AM	L 11.15 PM		L 6.00 AM	
BASS LAKE 1.5	6.5			Yard				11.15	11.30		6.15
ST. LOUIS PARK 2.5	8.0	SU			8.34	f 8.50	11.00				f 6.20
HOPKINS 3.2	10.5	KN	W42	48	8.37	f 8.54					s 6.40
(WEST END OF DOUBLE TRACK) (M & ST. L. CROSSING) TOWER E 14 4.5	13.7	WE		31 8.41	9.01	11.06	11.30 ⁷⁸	11.50			6.51
CHANHASSEN 2.8	18.2			13 f 9.05							f 7.00
HAZELTINE 5.0	21.0		122		8.48	9.08		11.40	12.05 PM		7.05
AUGUSTA 5.2	26.9		120	17	8.54	f 9.14 ²⁶⁴		11.47	12.15		f 7.15
COLOGNE 3.4	32.1	NY	117	200	8.59	f 9.20		11.55	12.25		s 7.45
BONGARDS 3.5	35.5			11 f 9.24							f 7.55
(M & ST. L. CROSSING) 0.5	39.0										
NORWOOD 5.5	39.5	UN	113	42	9.07	s 9.30 ¹⁸ 9.41		12.05 PM	12.35		s 8.05
PLATO 5.6	45.0	BA	23	22	9.12	f 9.47			12.45		f 8.20
GLENCOE 5.8	50.6	GN	267	210	s 9.22 ⁷⁸	s 10.09	11.39	12.30 ⁹²	1.15		s 8.40
SUMTER 4.5	56.4		116		9.29	10.16		12.38	1.25		8.57
BROWNTON 6.7	60.9	WN	143	41	9.34	f 10.21		12.45	1.35		s 9.20
STEWART 6.5	67.6	SY	123	49	9.41 ⁹¹	f 10.28		12.53	1.45		s 9.41 ¹⁷
BUFFALO LAKE 4.8	74.1	BO	83	49	9.47	f 10.35		1.01	1.55		s 10.00
HECTOR 9.0	78.9	HO	132	80	9.52	s 10.45		1.07	2.05		s 10.15 ⁹²
BIRD ISLAND 4.7	87.9	DS	133	262	10.01 ⁹²	f 11.01		1.30	2.35		s 11.30
OLIVIA 5.5	92.6	VI	85	53	s 10.09	f 11.15	12.14 AM	1.38	2.45		s 11.45
DANUBE 5.7	98.1	DU	117	34	10.15	f 11.22			1.45 ⁶ 3.10		s 12.05 PM
RENVILLE 6.9	103.8	XN	120	39	10.21	f 11.28		1.53 ⁷²	3.20		s 12.30
SACRED HEART 5.4	110.7	SA	139	41	10.28	f 11.36		2.02	3.30		s 12.50
MINNESOTA FALLS 2.2	116.1			17 10.33	11.43			2.10	3.45		f 1.00
(EAST END OF DOUBLE TRACK) E 118 1.6	118.3				10.35	11.45		2.14	4.00		1.05 ⁷²
GRANITE FALLS 2.0	119.9	G	18	44	f 10.38	s 12.36 AM	12.35 ⁵	2.18	4.30		f 1.20
(WEST END OF DOUBLE TRACK) E 122 (e. n. crossing) 8.0	121.9				10.41	12.39		2.25	4.40 ¹⁶		1.25
WEGDAHL 2.3	127.9	MR		23	10.47	f 12.45		2.35	4.50		f 1.35
ROCK CUT (EAST END OF DOUBLE TRACK) 2.9	130.2				10.50	12.47		2.39	5.05 ⁷⁸		1.38
MONTEVIDEO	138.1	MA		Yard	As 10.55 AM	As 1.00 AM	As 12.50 AM	2.45 PM	As 6.15 AM	A s 1.45 PM	

No. 15 and other passenger trains with diesel engines must not exceed maximum speed of 80 miles per hour. No. 17 must not exceed maximum speed of 75 miles per hour with F-6 engines. Other passenger trains must not exceed maximum speed of 70 miles per hour. Freight trains with S-2

or S-3 or diesel engines must not exceed maximum speed of 55 miles per hour, other freight trains 50 miles per hour. Maximum speed for F-5 and F-6 engines is 75 miles per hour, S-2 and S-3 engines 70 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

Double Track is in use between Minneapolis and Tower E 14, between E 118 and E 122 and between Rock Cut and Montevideo. Between E 118 and E 122, trains will keep to the LEFT, unless otherwise directed. Automatic Block System is in use between South Minneapolis and Montevideo. No. 15 when not displaying signals for a following section will register at Montevideo by register ticket. No. 15 will stop at Glencoe to get first class mail dispatched at Glencoe from No. 5 for No. 15.

Centralized Traffic Control is in use between east siding switch at Glencoe and Montevideo.

No. 17 will stop at Granite Falls to let off revenue passengers from Minneapolis or beyond or pick up revenue passengers for Spokane or west. No. 5 will hold at Granite Falls for U. S. Mail from G. N. No. 52, if that train arrives at G. N. station before No. 5 is due to leave.

Glen Lake Spur switch is located 1361 feet west of Tower E-14. No. 5 will stop at Norwood daily except Saturday.

FIRST SUBDIVISION—EASTWARD

3

TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Montevideo.	See Rule 6-A	Office Hours Also see page 11	FIRST CLASS			SECOND CLASS			THIRD CLASS	
				6	16	18	78	72	264	92	
				Passenger	Passenger	Passenger	Time Freight	Time Freight	Time Freight	Way Freight	
				Daily	Daily	Daily	Sunday only	Daily Except Sun.	Daily	Daily Except Sun.	
MINNEAPOLIS 1.9	133.1	BKOPR WXZ	Continuous	As 7.15 AM	As 6.20 AM	As 10.35 PM					
SOUTH MINNEAPOLIS 4.6	131.2	BCHJKOP RTWXYZ	Continuous	6.59	6.10	10.18	A 11.30 AM	A 8.00 PM	A 10.10 PM	As 3.30 PM	
BASS LAKE 1.5	126.6	HPVWX	No Office	6.40		10.07	11.15	7.10	9.55	3.18	
ST. LOUIS PARK 2.5	125.1	PVX	7.00 AM to 4.00 PM Except Sat. & Sun.	f 6.38	5.57	10.05	11.10	7.05	9.50	3.15	
HOPKINS 3.2	122.6	PV	7.30 AM to 5.00 PM Except Sat. & Sun.	f 6.30		10.03				s 3.10	
(WEST END OF DOUBLE TRACK) (M. & ST. L. CROSSING) TOWER E 14 4.5	119.4	IP	Continuous	6.21	5.51	10.00	11.00	6.45	9.38	2.40	
CHANHASSEN 2.8	114.9	P	No Office	s 6.13						f 2.25	
HAZELTINE 5.9	112.1	P	No Office	6.06		9.52	10.40	6.30	9.25	2.15	
AUGUSTA 5.2	106.2	P	No Office	f 5.55		9.46	10.30	6.15	9.14	f 1.52	
COLOGNE 3.4	101.0	BHJPWY	8.00 AM to 5.00 PM Except Sat. & Sun.	s 5.45	5.36	9.40	10.05	5.59	8.45	s 1.25	
BONGARDS 3.5	97.6		No Office	s 5.38						f 1.10	
(M. & ST. L. CROSSING) 0.5	94.1	I									
NORWOOD 5.5	93.6	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 5.30	5.26	9.32	9.40	5.45	8.25	s 1.00	
PLATO 5.8	88.1	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 5.10		9.27	9.30	5.30	8.12	f 12.45	
GLENCOE 5.8	82.5	BHJOPWX	Continuous	s 5.00	5.18	s 9.20	9.22	5.15	8.00	s 12.30 PM	
SUMTER 4.5	76.7	P	No Office	f 4.43		9.11	8.25	4.30	7.18	f 11.43	
BROWNTON 6.7	72.2	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 4.36		9.06	8.15	4.20	7.09	s 11.30	
STEWART 6.5	65.8	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 4.23		8.59	7.59	4.05	6.57	s 11.20	
BUFFALO LAKE 4.8	59.0	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 4.11		8.53	7.45	3.50	6.45	s 11.01	
HECTOR 9.0	54.2	P	8.00 AM to 5.00 PM Except Sat. & Sun.	f 4.01		8.48	7.35	3.35	6.30	s 10.15	
BIRD ISLAND 4.7	45.2	CHPWY	8.00 AM to 5.00 PM Except Sat. & Sun.	s 3.45		8.38	7.20	3.00	6.15	s 10.01	
OLIVIA 5.5	40.5	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 3.25	4.44	s 8.32	6.45	2.15	5.55	s 8.15	
DANUBE 5.7	35.0	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 3.10		8.23	6.35	2.05	5.46	s 8.00	
RENNILLE 6.0	29.3	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 3.00		8.17	6.25	1.53	5.37	s 7.45	
SACRED HEART 5.4	22.4	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 2.44		8.10	6.15	1.20	5.25	s 7.30	
MINNESOTA FALLS 2.2	17.0	HPW	No Office	2.35		8.04	6.00	1.08	5.10	f 7.05	
(EAST END OF DOUBLE TRACK) E 118 1.6	14.8	P	No Office	2.23		8.01	5.56	1.05	5.05	7.01	
NORTH GRANITE FALLS 2.0	13.2		Granite Falls 8.00 AM to 5.00 PM Except Sat. & Sun.			f 7.58					
(WEST END OF DOUBLE TRACK) E 122 (G. N. CROSSING) 6.0	11.2	IP	No Office	2.11	4.19	7.55	5.45	12.40	4.55	6.40	
WEGDAHL 2.3	5.2	P	8.00 AM to 5.00 PM Except Sat. & Sun.	s 2.02		7.49	5.30	12.30	4.45	s 6.30	
ROCK CUT (EAST END OF DOUBLE TRACK) 2.0	2.9	P	No Office	1.59		7.46	5.19	12.22	4.39	6.20	
MONTEVIDEO		BCHKPR TWX	Continuous	L 1.55 AM	4.07 AM	7.42 PM	5.10 AM	12.18 PM	4.30 PM	6.15 AM	

No. 16 and other passenger trains with diesel engines must not exceed maximum speed of 80 miles per hour. No. 18 must not exceed maximum speed of 75 miles per hour with F6 engines. Other passenger trains must not exceed maximum speed of 70 miles per hour. Freight trains with S-2

or S-3 or diesel engines must not exceed maximum speed of 55 miles per hour, other freight trains 50 miles per hour. Maximum speed for F-5 and F-6 engines is 75 miles per hour, S-2 and S-3 engines 70 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

Between Minneapolis and St. Louis Park, Inclusive, the General Supt., Superintendent, and Trainmaster of the Twin City Terminals Division have jurisdiction.

No. 18 will stop at North Granite Falls to let off revenue passengers from Spokane and points west.

No. 18 will stop at North Granite Falls on signal to pick up revenue passengers for Minneapolis and east.

No. 18 will reduce speed to 40 miles per hour passing Norwood depot for the dispatch of mail.

No. 6 will make regular stop at Granite Falls with departure time 2:20 A. M.

SECOND SUBDIVISION—WESTWARD

TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Montevideo	Telegraph calls	Capacity in cars	FIRST CLASS			SECOND CLASS			THIRD CLASS	
				5	17	15	63	263		93	
				Passenger	Passenger	Passenger	Time Freight	Time Freight		Way Freight	
				Daily	Daily	Daily	Daily	Daily		Daily Except Sun.	
MONTEVIDEO	1.4	MA	Yard	L 1.15 AM	L 11.00 AM	L 12.55 AM	L 7.30 AM	L 3.00 PM		L 6.30 AM	
SWIFT	1.4			1.20	11.02		7.35	3.05		6.35	
WEST END OF DOUBLE TRACK	5.0										
NORTH WATSON	6.4	W	135	63	1.36	11.08		7.43	3.12	f 6.50	
MILAN	15.6	RA	131	29	s 1.45	11.17		7.56	3.25	f 7.05	
APPLETON (G. N. CROSSING)	23.8	CA	163	230	s 1.57	f 11.25	1.16	8.15	3.40	s 7.30	
CORRELL	30.8	CR	119	30	s 2.07	11.33		8.25	3.50		s 7.45
ODESSA	39.4	DE	118	39	s 2.17	11.42		8.38	4.01		s 8.00
ORTONVILLE	45.8	RT	104	154	s 2.27	s 11.51	1.35	8.55	4.10		s 8.30
BIG STONE CITY	47.0	SJ	124		s 2.41	11.53		8.57	4.12		f 8.35
(EAST END OF DOUBLE TRACK)					E 80	3.01 ¹⁶					s 9.00 ⁶³
MILBANK	57.0	B	W115	Yard	s 3.14	s 12.13 PM	1.45	9.32	4.40		10.05
TWIN BROOKS	64.2	BK		48	s 3.27	12.21					f 10.20
MARVIN	71.9		W71	39	s 3.44	12.35					f 10.40
SUMMIT	79.1	H	W86	111	s 4.06	12.49	2.08	10.52	5.51		96
(WEST END OF DOUBLE TRACK)	4.2										s 11.20
JACKSON	83.3		102								
ORTLEY	87.1	RY		47	s 4.17	12.56		11.07	6.02		f 11.35
WAUBAY	92.5	WA	124	142	s 4.32	1.01		11.16	6.09		264 s 12.28 PM
WEBSTER	103.1	WS	177	184	s 4.55	s 1.14	2.28	11.50	6.30		s 1.05
HOLMQUIST	109.5	HM	125	17	s 5.02	1.20		12.03 ¹⁶ PM	6.40		f 1.20
(EAST END OF DOUBLE TRACK)	4.9				s 5.08	s 1.26					
BRISTOL	114.4	BR	E109 W71	184	5.24	1.31	2.39	12.25	7.00		s 2.35
ANDOVER	124.1	ND	E 73	237	s 5.44	1.41		12.55	7.25		s 3.25
(C. & N. W. CROSSING)											
GROTON	132.9	RO		45	s 5.59	1.50	2.56	1.25	7.50		18 s 4.35
(WEST END OF DOUBLE TRACK)	5.8										
JAMES	139.7			15	f 6.08	1.55		1.32	7.59		f 4.45
(EAST END OF DOUBLE TRACK)	5.3										
BATH	145.0	Q		15	f 6.15	2.00	3.06	1.40	8.10		s 4.55
(G. N. & C. & N. W. CROSSING)	7.2										
ABERDEEN	152.2										
(WEST END OF DOUBLE TRACK)	0.8										
ABERDEEN YARD	153.0	RN			As 6.35 AM	As 2.15 PM	As 3.18 AM	A 2.10 PM	A 8.50 PM		As 5.10 PM
	153.4		Yard								5.15 PM

No. 15 and other passenger trains with diesel engines must not exceed maximum speed of 80 miles per hour. No. 17 must not exceed maximum speed of 75 miles per hour with F-6 engines. Other passenger trains must not exceed maximum speed of 70 miles per hour. Freight trains

with S-2 or S-3 or diesel engines must not exceed maximum speed of 55 miles per hour, other freight trains 50 miles per hour. Maximum speed for F-5 and F-6 engines is 75 miles per hour, S-2 and S-3 engines 70 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

Double Track is in use between Montevideo and Swift, between Milbank and Summit, between Bristol and Groton and between Bath and Aberdeen yard.

Automatic Block System is in use between Montevideo and Aberdeen.

No. 15 when not displaying signals for a following section will register at Milbank by register ticket.

Centralized Traffic Control is in use between Montevideo and end of double track at Milbank.

Automatic Block System in use from end of double track at Aberdeen yard through Aberdeen yard. Rules 261, 263, and 264 are in effect.

No. 17 will stop at Appleton to let off revenue passengers from Minneapolis or beyond or pick up revenue passengers for Spokane or west.

Westward second and inferior class and extra trains will register at Aberdeen Yard instead of Aberdeen.

SECOND SUBDIVISION—EASTWARD

5

TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Aberdeen Yard	SEE RULE 6-A	Office Hours Also see Page 11	FIRST CLASS			SECOND CLASS		THIRD CLASS	
				16	18	6	264	78	96	94
				Passenger	Passenger	Passenger	Time Freight	Time Freight	Way Freight	Way Freight
				Daily	Daily	Daily	Daily	Saturday only	Daily Except Sun.	Daily Except Sun.
MONTEVIDEO 1.4	157.4	BCHKP RTWX	Continuous	As 4.02 AM	As 7.32 PM	As 1.45 AM	A 4.00 PM	A 3.30 AM		As 9.35 AM
SWIFT WEST END OF DOUBLE TRACK 5.0	156.0	PX	No Office		7.25	1.41	3.50	3.20		9.25
NORTH WATSON 9.2	151.0	P	Watson 8.00 AM to 5.00 PM Except Sat. & Sun.		7.20	1.36 ⁵	3.40	3.10		9.01
MILAN 8.2	141.8	P	8.00 AM to 5.00 PM Except Sat. & Sun.		7.10	s 1.27 ²⁶³	3.25	2.55		f 8.45
APPLETON (G. N. CROSSING) 7.0	133.6	HIPV WY	8.00 AM to 5.00 PM Except Sat. & Sun.	3.39	f 7.01	s 1.18 ¹⁵ s 12.55	3.12	2.35		s 8.15 ⁶³
CORRELL 8.6	126.6	P	8.00 AM to 5.00 PM Except Sat. & Sun.		6.53	s 12.43	3.00	2.12 ⁵ 1.54		f 7.45 ⁹³
ODESSA 6.4	118.0	P	8.00 AM to 5.00 PM Except Sat. & Sun.		6.44	s 12.32	2.45	1.43		f 7.30
ORTONVILLE 1.2	111.6	BHJP Y	8.00 AM to 4.00 PM Except Sunday 8.00 PM to 4.00 AM Except Sat. & Sun.		s 6.36	s 12.23	2.33	1.35 ¹⁵		s 7.15
BIG STONE CITY (EAST END OF DOUBLE TRACK) 10.0	110.4	P	7.00 AM to 4.00 PM Except Sat. & Sun.		6.30	s 12.15	2.30	1.18		f 6.30
MILBANK 7.2	100.4	BCHJKP RWXY	Continuous Except Sunday	3.10 ⁵	s 6.19	s 12.01 AM	2.00	1.00	As 12.30 PM	L 6.00 AM
TWIN BROOKS 7.7	93.2	P	8.00 AM to 5.00 PM Except Sat. & Sun.		6.06	s 11.40	1.30	12.15		f 11.45
MARVIN 7.3	85.5	P	No Office		5.58	s 11.28	1.15	12.01 AM		f 11.33 ⁶³⁻⁹³
SUMMIT (WEST END OF DOUBLE TRACK) 4.2	78.3	HPWY	8:00AM to 5:00PM Except Sat. & Sun.	2.50	263 5.51	s 11.18	12.49 ¹⁷	11.40	s 10.52	
JACKSON 3.8	74.1	P	No Office							
ORTLEY 5.4	70.8	P	8.00AM to 5.00PM Except Sat. & Sun.		5.41	s 11.08 ⁷⁸	12.38	11.15		f 10.30
WAUBAY 10.6	64.9	PW	8.00AM to 5.00PM Except Sat. & Sun.		5.36	s 11.00 ⁹³	12.28	11.05 ⁶ 10.50		s 10.15
WEBSTER 6.4	54.3	P	8.00AM to 8.00PM Except Sat. & Sun.	2.28 ¹⁵	s 5.25	s 10.44	12.13	10.31		s 9.45
HOLMQUIST 4.9	47.9	P	8.00AM to 5.00PM Except Sat. & Sun.		5.14	f 10.32 ⁶³	12.03 PM	10.05		f 8.55
BRISTOL 13.7	43.0	CHJP WXY	8:00AM to 11:59PM	2.12	5.07 s 5.02	s 10.25	11.50	9.55		s 8.45
ANDOVER 9.8	29.3	BJOPY	7.45AM to 4.45PM Except Sunday		4.44	s 9.58 ⁹³	10.50	9.10		s 7.25
(C. & N. W. CROSSING) GROTON (WEST END OF DOUBLE TRACK) 5.8	19.5	IPVW	8.00AM to 5.00PM Except Sat. & Sun.	1.52	4.34 ⁹³	s 9.43	10.30	8.40		s 6.55
JAMES 5.3	13.7	P	No Office		4.28	f 9.33	10.20	8.30		f 6.25
(EAST END OF DOUBLE TRACK) BATH 7.2	8.4	P	8.00AM to 5.00PM Except Sat. & Sun.	1.41	4.22	f 9.27	10.10	8.20 ²⁶³ s 6.15 ⁵		
(G. N. & C. & N. W. CROSSING) 0.8	1.2	I	No Office							
ABERDEEN 0.4	0.4	BKOPR VWX	Continuous	L 1.30 AM	L 4.10 PM	L 9.15 PM	L 9.50 AM	L 8.05 PM	L 6.00 AM	
(WEST END OF DOUBLE TRACK) ABERDEEN YARD		BCHJKP TVWXYZ	No Office				9.45 AM	8.00 PM	5.45 AM	

No. 16 and other passenger trains with diesel engines must not exceed maximum speed of 80 miles per hour. No. 18 must not exceed maximum speed of 75 miles per hour with F6 engines. Other passenger trains must not exceed maximum speed of 70 miles per hour. Freight trains with S-2

or S-3 or diesel engines must not exceed maximum speed of 55 miles per hour, other freight trains 50 miles per hour. Maximum speed for F-5 and F-6 engines is 75 miles per hour, S-2 and S-3 engines 70 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

Connecting Track in service between North Watson Siding and Watson House Tracks.

No. 18 will stop at Appleton to let off revenue passengers from Spokane and points beyond and to pick up revenue passengers for Minneapolis and points beyond.

No. 16 when not displaying signals for a following section will register at Milbank and Montevideo by register ticket.

No. 6 will stop at Marvin daily except Sunday.

THIRD SUBDIVISION—WESTWARD

TIME TABLE No. 17	September 30, 1951	STATIONS	Distance from Aberdeen	Telegraph calls	Capacity in cars	FIRST CLASS			SECOND CLASS		Time Freight
						15	5	17	263		
						Passenger	Passenger	Passenger	Daily	Daily Except Sun.	
ABERDEEN	0.4			RN		L 3.33 AM	L 7.20 AM	L 2.30 PM			
(WEST END OF DOUBLE TRACK)											
ABERDEEN YARD	0.4				Yard		7.22	2.31	L 10.45 PM		
7.4							7.32	2.40	11.00		
FIFE	7.8				108						
5.3											
MINA	13.1			MX	112	27		s 7.40	2.46	11.10	
8.1											
CRAVEN	21.2				109	16		f 7.50	2.55	11.25	
5.3											
IPSWICH	26.5			P	82	35		s 8.02	f 3.01	11.45	
8.1											
BEEBE	34.6				79	16		s 8.13	3.12 ¹⁸	12.05 AM	
6.5											
ORIENT LINE JUNCTION	41.1						8.20	3.18			
0.5											
ROSCOE	41.6			RC	108	133	4.10	s 8.28	f 3.21 ⁷⁸	12.30 ¹⁶ 1.00	
8.6											
GRETNNA	50.2				109	18		f 8.40	3.31	1.25	
6.7											
BOWDLE	56.9			BW	108	45	4.23 ²⁶⁴	s 8.54	f 3.39	1.45	
3.5											
BOWDLE GRAVEL PIT	60.4						8.58	3.43	1.50		
4.1											
ALAMO	64.5				81		9.04	3.48	2.05		
5.8							9.12				
JAVA JUNCTION	69.8				82		9.23	3.55	2.20		
JAVA				JA		35	s 9.17				
7.8											
SELBY	77.1			SB	107	27	s 9.38	f 4.03	2.35		
8.0											
SITKA	85.1				93	18	f 9.50	4.11 ²⁶⁴	2.65		
4.3											
GLENHAM	89.4			G	166	80	s 9.59	4.17	3.15		
8.8											
MOBRIDGE	98.2			MB	Yard	As 5.05 AM	As 10.15 AM ⁷⁸	As 4.30 PM	A 4.00 AM		

No. 15 and other passenger trains with diesel engines must not exceed maximum speed of 80 miles per hour. No. 17 must not exceed maximum speed of 75 miles per hour with F6 engines. Other passenger trains must not exceed maximum speed of 70 miles per hour. Freight trains with S-2

or S-3 or diesel engines must not exceed maximum speed of 55 miles per hour, other freight trains 50 miles per hour. Maximum speed for F-5 and F-6 engines is 75 miles per hour, S-2 and S-3 engines 70 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

Automatic Block System is in use between the west end of double track at Aberdeen Yard and Mobridge. Rules 261, 263 and 264 are in effect.

Double track is in use between Aberdeen and Aberdeen Yard.

Clock at Mobridge marked CENTRAL TIME must be observed.

First class trains will not register at Aberdeen Yard.

Third Subdivision westward trains starting at Aberdeen Yard will secure Clearance Form A at Aberdeen. Rule 83 (B) does not apply at Aberdeen Yard.

EMERGENCY TELEPHONES

Dispatchers' Telephone

Bass Lake..... In office at west end of yard.
Hopkins..... In freight room.
Chanhassen..... In depot.
Montevideo..... On pole at Swift Crossing at Stock Yd.
Marvin..... In waiting room.
Summit..... Gravel Track 2700 ft. east of the west switch.
Andover Fill..... On pole.
Aberdeen..... On pole opposite water tank west of passenger station.
Glenham..... At west end of siding.
Mobridge..... At east yard switch.

At all Stop Signals in single track Automatic Block territory.

At all switches on main track in C. T. C. and C. A. B. territory.

Portable telephones in locker on baggage car on Nos. 17 and 18 and in locker in baggage end of dormitory car on 15 and 16.

Block Telephone

In switchtenders' shanty near Cedar Ave.
South Minneapolis. { At Fifth Ave. on pole.
At Elliot Ave. on pole.
Humboldt Ave..... On pole.
Bass Lake..... In office at east end of yard.
Plato..... In waiting room.
Milbank..... At west end of yard on pole.
Aberdeen..... At G. N. crossing.
Sitka..... In depot.

THIRD SUBDIVISION—EASTWARD

7

TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Mobridge	SEE RULE 6-A	Office Hours Also See Page 11	FIRST CLASS			SECOND CLASS		
				16	18	6	264	78	
				Passenger	Passenger	Passenger	Time Freight	Time Freight	
				Daily	Daily	Daily Except Sun.	Daily	Saturday Only	
ABERDEEN 0.4 (WEST END OF DOUBLE TRACK)	98.2	BKOPRVWX	Continuous	As 1.15 AM	As 3.55 PM	As 8.20 PM			
ABERDEEN YARD 7.4	97.8	BCHJKP RTVWXYZ	No Office		3.47	8.07	A 6.15 AM	A 6.00 PM	
FIFE 5.3	90.4		No Office		3.38	f 7.57	6.00	5.20	
MINA 8.1	85.1	P	8.00AM to 5.00PM Except Sat. & Sun.		3.33	s 7.48	5.50	5.05	
CRAVEN 5.8	77.0	HPW	No Office		3.25	f 7.36	5.35	4.25	
IPSWICH 8.1	71.7	P	8.00AM to 5.00PM Except Sat. & Sun.		f 3.20	s 7.27	5.25	4.05	
BEEBE 6.5	63.6		No Office		3.12 ¹⁷	s 7.14	5.10	3.45	
ORIENT LINE JUNCTION 0.5	57.1	J	No Office						
ROSCOE 8.6	56.6	BCHJPWXY	8.00AM to 5.00PM Except Sunday	263 12.35	f 3.01 ⁷⁸	s 6.54	4.55	3.30 ¹⁷ - 2.05 ¹⁸	
GRETNA 6.7	48.0	P	No Office		2.51	f 6.44	4.35	1.50	
BOWDLE 3.5	41.8	HPW	8.00AM to 5.00PM Except Sat. & Sun.		f 2.43	s 6.36	4.25 ¹⁵ 4.05	1.35	
BOWDLE GRAVEL PIT 4.1	37.8	PY	No Office		2.39	6.27	3.55	1.15	
ALAMO 5.3	33.7	P	No Office		2.35	6.23	3.45	1.00	
JAVA JUNCTION 28.4		PX	No Office		2.28	6.15 6.04	3.30	1.45 1.16	
JAVA 7.3		PX	8.00AM to 5.00PM Except Sat. & Sun.			s 6.07		12.40	
SELBY 8.0	21.1	PW	8.00AM to 5.00PM Except Sat. & Sun.		f 2.18	s 5.50	3.10	12.01 PM	
SITKA 4.3	13.1	P	No Office		2.07	f 5.38	2.55	11.22	
GLENHAM 8.8		P	8.00AM to 5.00PM Except Sat. & Sun.		2.01	s 5.28	2.50	11.10	
MOBRIDGE		BCKPRTWXZ	Continuous	L 11.40 PM	L 1.50 PM	L 5.15 PM ¹⁷	L 2.15 AM	L 10.45 PM ⁵	

No. 16 and other passenger trains with diesel engines must not exceed maximum speed of 80 miles per hour. No. 18 must not exceed maximum speed of 75 miles per hour with F6 engines. Other passenger trains must not exceed maximum speed of 70 miles per hour. Freight trains with S-2

or S-3 or diesel engines must not exceed maximum speed of 55 miles per hour, other freight trains 50 miles per hour. Maximum speed for F-5 and F-6 engines is 75 miles per hour, S-2 and S-3 engines 70 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

TONNAGE RATINGS

STATIONS	S-2 Eng.	L-3 Eng.	L-2 Eng.	STATIONS	S-2 Eng.	L-3 Eng.	L-2 Eng.
WESTWARD				EASTWARD			
Minneapolis to Bird Island.....	4750	3700	3200	Mobridge to Roscoe.....	4800	3700	3200
Bird Island to Montevideo.....	7000	6000	5500	Mobridge to Roscoe (helper Mobridge to Alamo).....	5000	5000	5000
Montevideo to Milbank.....	5000	4200	3500	Roscoe to Aberdeen.....	9000	8000	6500
Milbank to Summit.....	2700	1800	1400	Aberdeen to Bristol.....	4500	3680	3200
Milbank to Summit (helper).....	4200	3300	2800	Aberdeen to Bristol (helper Groton to Bristol).....	7000	6000	5000
Summit to Aberdeen.....	7000	6000	5500	Bristol to Summit.....	5400	4200	3600
Aberdeen to Java Junction.....	3800	2900	2300	Bristol to Summit (helper Waubay to Summit).....	7000	6000	5000
Java Junction to Mobridge.....	7000	5500	4800	Summit to Montevideo.....	7000	6000	5500
Farmington to Cologne.....			1600	Montevideo to Bird Island.....	5800	4300	3800
Mitchell to Ashton.....			5000	Montevideo to Bird Island (helper Tower E-122 to Minn. Falls).....	7000	6000	5500
Ashton to Aberdeen.....			6000	Bird Island to Minneapolis.....	7000	6000	5500

Chief Dispatcher may increase or decrease above ratings according to conditions.

WESTWARD—FOURTH SUBDIVISION—EASTWARD

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Farmington	TIME TABLE No. 17 September 30, 1951 STATIONS		Distance from Cologne	SEE RULE 6-A	Office Hours Also see page 11	THIRD CLASS	
	205	Sidings	Other tracks								206	
	Mixed										Mixed	
	Daily Except Sun.										Daily Except Sun.	
L 9.55 AM			Yard	F		(C. M. ST. P. & P. CROSSING) FARMINGTON	4.8	38.0B	BCHIJP RVWXY	Continuous	As 3.30 PM	
s10.10	37	32	FN	4.8		(M. N. & S. CROSSING) LAKEVILLE	10.8	33.2	MP	8.00AM to 5.00PM Except Sunday	s 3.15	
s10.35	24	10	K	15.6		PRIOR LAKE	8.4	22.4	P	8.00AM to 5.00PM Except Sat. & Sun.	s 2.35	
s11.20	31	48	SX	24.0		(C. ST. P. M. & O. CROSSING) SHAKOPEE	3.9	14.0	MPV	8.00AM to 5.00PM Except Sat. & Sun.	s 2.10	
s11.35	28	31	MS	27.9		(M. & ST. L. CROSSING) CHASKA	10.1	MPVX	MPVX	8.00AM to 5.00PM Except Sat. & Sun.	s 1.50	
As 12.15 PM		Yard	NY	38.0		COLOGNE			BHJPRWXY	8.00AM to 5.00PM Except Sunday.	L 1.15 PM	

Trains must not exceed maximum speed of 30 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

WESTWARD—FIFTH SUBDIVISION—EASTWARD

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Glenoce	TIME TABLE No. 17 September 30, 1951 STATIONS		Distance from Hutchinson	SEE RULE 6-A	Office Hours Also see Page 11	THIRD CLASS	
	315	Sidings	Other tracks								392	
	Mixed										Mixed	
	Daily Except Sun.										Daily Except Sun.	
L 10.45 AM			Yard	GN		GLENCOE	7.4	13.8	BHJOPRWX	Continuous	As 1.10 PM	
s11.05	18				7.4	BISCAY	6.4			No Office	s 12.46	
As 11.25 AM		Yard	HN	18.8		HUTCHINSON			RT	7.15AM to 4.15PM Except Sat. & Sun.	L 12.30 PM	

Trains must not exceed maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

WESTWARD—SEVENTH SUBDIVISION—EASTWARD

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Milbank	TIME TABLE No. 17 September 30, 1951 STATIONS		Distance from Sisseton	SEE RULE 6-A	Office Hours Also see Page 11	THIRD CLASS	
	505	Sidings	Other tracks								516	
	Mixed										Mixed	
	Daily Except Sun.										Daily Except Sun.	
L 10.00 AM			Yard	B		MILBANK	10.1	37.1	BCHJKORWXY	Continuous	As 3.45 PM	
s10.30	31			CO	10.1	CORONA	6.9			8.00AM to 5.00PM Except Sat. & Sun.	s 2.55	
s11.05	43			MO	17.0	WILMOT	10.4	20.1		8.00AM to 5.00PM Except Sat. & Sun.	s 2.30	
s11.35	27			PV	27.4	PEEVER	9.7			8.00AM to 5.00PM Except Sat. & Sun.	s 2.00	
As 12.15 PM		Yard	SI	37.1		SISSETON			RT	8.00AM to 5.00PM Except Sat. & Sun.	L 1.30 PM	

Trains must not exceed maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

WESTWARD—SIXTH SUBDIVISION—EASTWARD

9

THIRD CLASS		Capacity in cars		Telegraph calls	Distance from Ortonville	TIME TABLE No. 17 September 30, 1951		Distance from Fargo	SEE RULE 8-A	Office Hours Also see Page 11	THIRD CLASS	
	463	Sidings	Other tracks			STATIONS					464	
	Mixed										Mixed	
	Daily Except Sat.										Daily Except Sun.	
L 9.45 AM			Yard	RT			ORTONVILLE 2.5	118.2	BHJRXY	8.00AM to 4.00PM Except Sun. 8.00PM to 4.00AM Except Sat. & Sun.	As 5.00 PM	
			16		2.5		DOUBLING TRACK 10.9	115.7		No Office		
s 10.30	43			V	13.4		CLINTON	104.8		8.00AM to 5.00PM Except Sat. & Sun.	f 4.25	
s 11.00	33	17	GR	21.2			GRACEVILLE (G. N. CROSSING) 7.8	97.0	HVW	8.00AM to 5.00PM Except Sat. & Sun.	s 3.40	
f 11.15			8		26.5		COLLIS 5.0	91.7		No Office	f 3.10	
f 11.30	37			DU	31.5		DUMONT 7.1	86.7		8.00AM to 5.00PM Except Sat. & Sun.	f 2.50	
s 11.50 12.01 PM	56	29	WH	38.6			WHEATON 9.1	79.6		8.00AM to 5.00PM Except Sunday	s 2.30	
⁴⁶⁴ f 12.35	33	33	WR	47.7			WHITE ROCK 4.3	70.5		8.00AM to 5.00PM Except Sat. & Sun.	⁴⁶³ f 12.35	
f 1.15		16			52.0		BLACKMER 5.5	66.2		No Office	f 12.20	
s 1.35	43	15	MT	57.5			FAIRMOUNT 0.3	60.7	C	8.00AM to 5.00PM Except Sat. & Sun.	s 12.01 PM	
					57.8		(SOO LINE CROSSING) 0.5	60.4	V	No Office		
					58.8		(G. N. CROSSING) 5.6	59.9		No Office		
f 1.55	48				63.9		TYLER 7.5	54.3		No Office	f 11.00	
					71.4		(N. P. CROSSING) 0.4	46.8	V	No Office		
					71.8		(G. N. CROSSING) 0.3	46.4	MV	No Office		
s 2.45	33	27	AP	72.1			WAHPETON 1.4	46.1	HW	8.00AM to 5.00PM Except Sunday	s 10.30	
		102			73.5		OTTERTAIL SPUR 2.4	44.7	Y	No Office		
					75.9		(G. N. CROSSING) 10.3	42.3	I	No Office		
s 3.45	38		AO	86.2			ABERCROMBIE 3.9	32.0		8.00AM to 5.00PM Except Sat. & Sun.	s 8.15	
f 4.00		8			90.1		ENLOE 5.8	28.1		No Office	f 8.03	
f 4.30	27		CN	95.9			CHRISTINE 2.8	22.3		7.30AM to 4.30PM Except Sat. & Sun.	f 7.50	
f 4.40		9			98.7		LITHIA 3.8	19.5		No Office	f 7.35	
f 5.00	29		HS	102.5			HICKSON 5.4	15.7		7.00AM to 4.00PM Except Sat. & Sun.	f 7.25	
f 5.20	26		WI	107.9			WILD RICE 9.0	10.3		7.00AM to 2.00PM Except Sat. & Sun.	f 7.10	
					116.9		(N. P. CROSSING) 0.2	1.8		No Office		
					117.1		(N. P. CROSSING) 1.1	1.1	IV	No Office		
As 6.30 PM		Yard	FO	118.2			FARGO		CRTWX	6.30AM to 3.30PM Except Sat. & Sun.	L 6.45 AM	

Trains handling passenger equipment only must not exceed maximum speed of 30 miles per hour; other trains 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

NINTH SUBDIVISION—WESTWARD

TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Mitchell	Telegraph calls	Capacity in cars	FIRST CLASS			SECOND CLASS		
				123		61	Time	Freight	
				Sidings	Other tracks	Passenger	Daily	Daily	
Mitchell 7.5		S		Yard	L	7.45 PM		L	10.00 AM
LOOMIS 7.5	7.5		26			7.55			10.20
LETCHER 6.8	15.0	R	56	63	s	8.05			108 11.00
CUTHBERT 6.4	21.8		45		f	8.15			64 11.15
WOONSOCKET 9.7	28.2	KN	65	104	s	8.28			11.35
ALPENA 8.2	37.9	A	95	38	s	8.43			11.50
VIRGIL 8.5	46.1	GI	73	24	s	8.55			12.05 PM
WOLSEY (C. & N. W. CROSSING)	54.6	WO	30	38	s	9.15			12.22
BONILLA 4.7	67.0	BN	79	32	s	9.35			12.50
SPOTTSWOOD 6.0	71.7		21			9.42			1.05
TULARE 7.9	77.7	RI	56	83	s	9.52			1.20
(C. & N. W. CROSSING) 2.2	85.6								
(C. & N. W. CROSSING) REDFIELD	87.8	FD	91	25	s	10.08			2.00
ASHTON 5.2	96.0	RS	85	32	s	10.25			2.20
GALLUP 5.8	101.2		21			10.34			2.30
MELLETTE 5.9	107.0	NE	30	35	s	10.45			2.50
DUXBURY 5.8	112.9		23			10.55			3.10
WARNER 6.9	118.7	RD	56	88	s	11.05			3.30
(C. & N. W. CROSSING) 2.0	125.6								
(M. & ST. L. CROSSING) 1.0	127.6					11.20			
ABERDEEN	128.6	RN		Yard	As	1.40 PM		A	4.00 PM

Passenger trains must not exceed maximum speed of 60 miles per hour; other trains 40 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

Manual Block System is in use Between Aberdeen and Mitchell.

Rule 319A Applies at Aberdeen, Woonsocket and Mitchell.

Westward second and inferior class and extra trains will register at Aberdeen instead of Aberdeen.

WESTWARD—EIGHTH SUBDIVISION—EASTWARD

SECOND CLASS 605	Capacity in cars	Telegraph calls	Distance from Andover.	TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Brampton	SEE RULE 6-A	Office Hours Also see Page 11	THIRD CLASS 606	
								Mixed	
								Daily Except Sun.	
L 8.30 AM		Yard	ND	ANDOVER 7.3	42.9	BCJRY	7.45AM to 4.45PM Except Sunday	As 3.00 PM	
s 9.00	40		PR	PIERPONT 7.6	35.6		8.00AM to 5.00PM Except Sat. & Sun.	s 2.40	
s 9.35	53		FA	LANGFORD 7.2	28.0		8.00AM to 5.00PM Except Sat. & Sun.	s 2.05	
s 9.57	29			SPAIN 6.3	20.8		No Office	s 1.25	
s 10.50	59	34	BI	BRITTON 4.0	14.5	HWY	8.00AM to 5.00PM Except Sat. & Sun.	s 1.10 PM	
				(G. N. CROSSING) 6.0	10.5		No Office		
s 11.20	24			NEWARK 4.5	4.5		No Office	s 11.59	
As 11.35 AM	606	Yard	BM	BRAMPTON		RY	8.00AM to 5.00PM Except Sat. & Sun.	L 11.45 AM	

Trains must not exceed maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

NINTH SUBDIVISION—EASTWARD

11

TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Aberdeen	SEE RULE 6-A	Office Hours Also see Page 11 Below	FIRST CLASS			SECOND CLASS		
				108			64	62	
				Passenger			Time Freight	Time Freight	
				Daily			Daily	Saturday only	
Mitchell	128.6	BCJKORTWX	Continuous	As 11.30 AM			A 12.30 PM	A 5.00 PM	
7.5			No Office	\$ 11.15			12.05 PM	4.20	
Loomis	121.1		8.00 AM to 5.00 PM Except Sat. & Sun.	⁶¹ \$ 11.00			11.45	4.00	
7.5			No Office	\$ 10.49			⁶¹ 11.15	3.35	
Letcher	113.6		8.00 AM to 5.00 PM Except Sat. & Sun.	\$ 10.25			11.00	3.10	
6.8			8.00 AM to 5.00 PM Except Sat. & Sun.	⁶⁴ \$ 10.05			10.15 ¹⁰⁸ 9.48	2.05	
Cuthbert	106.8		8.00 AM to 5.00 PM Except Sat. & Sun.	s 9.50			9.30	1.40	
6.4			8.00 AM to 5.00 PM Except Sat. & Sun.	\$ 9.35			9.05	1.20	
Woonsocket	100.4	HJRWXY	8.00 AM to 5.00 PM Except Sat. & Sun.	\$ 9.12			8.25	12.40	
9.7			8.00 AM to 5.00 PM Except Sat. & Sun.	f 8.59			7.55	12.10 AM	
Alpena	90.7		8.00 AM to 5.00 PM Except Sat. & Sun.	s 8.45			7.30	11.55	
8.2			No Office						
Virgil	82.5		8.00 AM to 5.00 PM Except Sat. & Sun.						
8.5			8.00 AM to 5.00 PM Except Sat. & Sun.						
Wolsey	74.0	IV	8.00 AM to 5.00 PM Except Sat. & Sun.						
(C. & N. W. CROSSING)	12.4		8.00 AM to 5.00 PM Except Sat. & Sun.						
Bonilla	61.6	CHWX	8.00 AM to 5.00 PM Except Sat. & Sun.						
4.7			No Office						
Spotswood	56.9		8.00 AM to 5.00 PM Except Sat. & Sun.						
6.0			No Office						
Tulare	50.9		8.00 AM to 5.00 PM Except Sat. & Sun.						
7.9			No Office						
(C. & N. W. CROSSING)	48.0	I	No Office						
2.2									
(C. & N. W. CROSSING)	40.8	IV	8.00 AM to 5.00 PM	s 8.30			7.10	11.25	
Redfield	8.2		8.00 AM to 5.00 PM Except Sat. & Sun.	s 8.10			6.40	¹²³ 10.25	
Ashton	32.6	HW	No Office	f 8.00			6.20	10.00	
5.2			8.00 AM to 5.00 PM Except Sat. & Sun.	s 7.50			5.55	9.50	
Gallup	27.4		No Office	s 7.40			5.35	9.30	
5.8			8.00 AM to 5.00 PM Except Sat. & Sun.	s 7.30			5.20	9.15	
Mellette	21.6		No Office						
5.0									
Duxbury	15.7		No Office						
5.8									
Warner	9.9		8.00 AM to 5.00 PM Except Sat. & Sun.						
6.9			No Office						
(C. & N. W. CROSSING)	8.0	I	No Office						
2.0			No Office						
(M. & ST. L. CROSSING)	1.0	M	Continuous	L 7.15 AM			L 5.00 AM	L 8.45 PM	
ABERDEEN		BCHJKO RTVWXYZ							

Passenger trains must not exceed maximum speed of 60 miles per hour; other trains 40 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

Woonsocket is Register Station for First Class Trains only

OFFICE HOURS NOT OTHERWISE SHOWN.

Station	Saturday	Sunday	Holiday
Milbank.....	Continous	12:01 am to 4:01 pm	Continous
Ortonville.....	8:00 am to 4:00 pm	None	None
Andover.....	7:45 am to 4:45 pm	None	None

WESTWARD—TENTH SUBDIVISION—EASTWARD

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Aberdeen	TIME TABLE No. 17		Distance from Edgeley	SEE RULE 6-A	Office Hours Also see Page 11	THIRD CLASS			
705	Mixed	Sidings	Other tracks			September 30, 1951 STATIONS		7.8	56.1	51.1	45.2	38.3	63.9	706
	Daily Except Sun.					ABERDEEN								
L	8.15 AM		Yard	RN		GAGE								
f	8.35	18			7.8	5.0								
s	8.50	27		V	12.8	5.9								
s	9.07	29		BR	18.7	6.9								
s	9.30	35	26	DK	25.6	6.2								
f	9.48	24			31.8	WINSHIP								
s	10.15	38	39	DA	37.4	ELLENDALE								
f	10.31	24			42.3	(G. N. CROSSING)								
s	10.48		17		48.6	DUANE								
s	10.55	80		MA	49.8	(500 LINE CROSSING)								
f	11.13				56.9	MONANGO CROSSING								
						MONANGO								
						7.1								
						POTTS								
						7.0								
						EDGELEY								
	As 11.30 AM		Yard	GY	63.9									

Trains must not exceed maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

WESTWARD—ELEVENTH SUBDIVISION—EASTWARD

SECOND CLASS		Capacity in cars		Telegraph calls	Distance from Orient	TIME TABLE No. 17		Distance from Roscoe	SEE RULE 6-A	Office Hours Also see Page 11	SECOND CLASS		
971	Mixed	Sidings	Other tracks			September 30, 1951 STATIONS		9.3	9.8	11.6	12.3	0.5	972
	Tues. and Sat. only					ORIENT							
L	4.40 PM		Yard	RY		(C. & N. W. CROSSING)	9.3						
s	5.10	33	15	FN	9.8	FAULKTON	9.3						
f	5.40		9		20.9	NORBECK	11.6						
f	6.10	27			29.0	8.1							
A	6.40 PM				40.8	LOYALTON	11.8						
	6.45 PM		Yard	RC	41.3	ORIENT LINE JUNCTION	0.5						
						ROScoe							

Trains must not exceed maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

This time-table confers no authority between Roscoe and Orient Line Jct. Third subdivision time-table governs. Eleventh subdivision eastward trains will obtain Clearance Form A at Roscoe instead of Orient Line Jct. Rule 83B.

Rule 83B does not apply at Orient when operator not on duty if train order signal indicates proceed as per Rule 200C.

THIRD CLASS		Capacity in cars		Telegraph calls	Distance from Roca	TIME TABLE No. 17 September 30, 1951 STATIONS	Distance from Linton	SEE RULE 6-A	THIRD CLASS	
	805	Sidings	Other tracks						806	
	Mixed								Mixed	
	Daily Except Sun.								Daily Except Sun.	
L 9.00 AM			Yard	RC		ROSCOE —11.1	75.3	BCHJPRWXY	8.00AM to 5.00PM Except Sunday	As 1.15 PM
s 9.40	50	18	HM	11.1		HOSMER —7.2	64.2		8.00AM to 5.00PM Except Sat. & Sun.	s 12.50
s 10.10	31		H	18.3		HILLSVIEW —8.0	57.0	HW	8.00AM to 5.00PM Except Sat. & Sun.	s 12.20 PM
s 10.80						EUREKA —10.8	49.0		8.00AM to 5.00PM Except Sat. & Sun.	s 11.50 805
s 11.10	39	40	K	26.3		GREENWAY —1.5	38.2	W	8.00AM to 5.00PM Except Sat. & Sun.	s 11.10
s 11.35	26		W	37.1		(SOO LINE CROSSING) MADRA —6.5	36.7	V	No Office	s 10.30
s 11.50		8		38.6		ZEELAND —9.0	30.2		8.00AM to 5.00PM Except Sat. & Sun.	s 10.20
s 12.10 PM	39		Z	45.1		HAQUE —11.2	21.2	C	8.00AM to 5.00PM Except Sat. & Sun.	s 10.00
s 12.50	27	8	AU	54.1		STRASBURG —10.0	10.0		8.00AM to 5.00PM Except Sat. & Sun.	s 9.20
s 1.30	28	6	B	65.3		LINTON		RVWXY	7.45AM to 4.45PM Except Sat. & Sun.	s 8.35
As 2.00 PM			Yard	ON	75.3				L 8.00 AM	

Trains must not exceed maximum speed of 25 miles per hour.

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.

YARD LIMITS AT

Minneapolis.....	Extend from M. P. 433 about 6600 ft. west of Hopkins station to Minneapolis passenger depot.	Fargo.....	Extend from 5463 feet east of east switch of N. P. Interchange tracks and include all tracks west thereof.
Cologne.....	Extend from 2000 feet east of east yard switch on Fourth subdivision to junction with First subdivision.	Roscoe.....	Extend from 1980 feet east of east wye switch to 2000 feet west of west switch of siding on Third subdivision and from south switch of wye to 5280 ft. east on 11th subdivision and to 5280 ft. west of yard switch on 12th subdivision.
Glencoe.....	Extend from 1000 feet east of east switch of siding to west switch of siding.	Java Jet. and Java..	Extend from clearance point at junction switch to end of main track on Java Line at Java.
Bird Island.....	Extend from 1000 feet east of east switch of siding to 1000 feet west of west switch of No. 1 yard track.	Mobridge.....	Extend from 2170 feet east of east switch of east yard to 2640 feet west of west switch.
Montevideo.....	Extend from 3867 feet east of east crossover switch to 3303 feet west of double track at Swift.	Farmington.....	Extend from 5280 feet west of west wye switch to end of main track Farmington Yard.
Milbank.....	Extend from switch at end of double track east of Milbank to 3000 feet west of west cross-over switch on Second Subdivision and to 2000 feet west of the Wye switch on Seventh Subdivision.	Chaska.....	Extend from 3450 feet east of east switch of house track to 4000 feet west of M. & St. L. crossing.
Ortonville.....	From junction switch to 3000 feet west of the doubling track switch on Sixth Subdivision.	Mitchell.....	Extend from depot to 1800 feet west of west switch of west yard.
Bristol.....	Extend from 3362 feet east of end of double track to 6600 feet west of west crossover switch.	Woonsocket.....	Extend from 3790 feet east of east switch of siding to 2716 feet west of west switch of siding.
Aberdeen and Aberdeen Yard.....	Extend from 3400 feet east of G. N. & C. & N. W. crossing to 4624 feet west of the west switch of Aberdeen yard and from 700 feet east of Siebrecht Spur on Ninth subdivision to 1200 feet west of switch of Fair Ground track on the Tenth subdivision.	Bonilla.....	Extend from 6000 feet east of coaling station to 5000 feet west of coaling station.
		Edgeley.....	Extend from 3790 feet east of east switch of siding to depot.
		Linton.....	Extend from 3900 feet east of east wye switch to depot.

COMPANY SURGEONS ARE LOCATED AS FOLLOWS:

Location	Name	Telephone	Location	Name	Telephone
Chicago.....	§‡A. R. Metz, Chief Surgeon Union Station §‡Raymond Householder, Asst. Chief Surgeon Wesley Memorial Hospital, 240 E. Superior Street, DElaware 7-6500. Dr. Wm. F. Munson, Asst. to Chief Surgeon. L. F. McBride, Aurist, 122 So. Michigan Ave., Wabash 2272. §*Virgil Wescott, Oculist, 30 N. Michigan Ave., DEarborn 2-3127. H. A. Hooper, Dentist, 53 E. Washington St., State 0509.		Waubay.....	A. P. Hawkins, Office, 9 W, Res., 9W. W. H. Karlins, Office 5, Res., 195.	
Minneapolis...	§‡O. W. Yoerg, Office, 1853 Medical Arts Bldg., Geneva 1700, Res., Colfax 1606. Dr. William H. Rucker, Office, 1853 Medical Arts Building, GE 1700, Res. HY 0839. §Dr. Frank J. Cavanor, Oculist, 1818 Medical Arts Bldg., Office, BR 8701, Res., KE 2761. After 5:00 PM injured employees should be sent to Northwestern Hospital.		Webster.....	R. G. Mayer, Office, 4434, Res., 4143. ‡E. A. Pittenger, Office, 2411, Res. 2435. ‡Owen King, Office, 2541, Res., 2808. Carson B. Murdy, Office, 3636, Res., 4054.	
Norwood.....	J. D. Selmo, Office, 152, Res., 152.		Aberdeen.....	J. D. Alway, Oculist, Office, 2525, Res., 2131. Dr. Paul V. McCarthy, Roentgenologist, Office, 4168, Res. 2823.	
Glencoe.....	*H. H. Holm, Office, 170, Res., 303. John W. Gridley, Asst., Office 170. Res. 9.		Ipswich.....	*G. J. Bloemendaal, Office, 4311, Res., 4311.	
Stewart.....	W. W. Klima, Office, 30, Res., 42.		Selby.....	W. A. George, Office, 54-W, Res., 54-J.	
Hector.....	Chester A. Anderson, Office 9, Res. 9-2.		Mobridge.....	*A. W. Spiry, Office, 444, Res. 574.	
Bird Island...	*H. P. Hinderacker, Office, 141, Res., 236.		Farmington...	*J. A. Sanford, Office, 128A, Res., 128A.	
Olivia.....	§J. A. Cosgriff, Office, 84, Res., 343. J. A. Cosgriff, Jr., Office, 84, Res., 343.		Graceville.....	I. L. Oliver, Office, 18, Res., 215.	
Renville.....	A. Maxwell Fawcett, Office, 99, Res., 96.		Wheaton.....	*A. L. Lindberg, Office, 20, Res., 20-J.	
Sacred Heart.	J. Dordal, Office, 27, Res., 55. H. E. Peterson, Office, 29, Res., 358.		Wahpeton.....	*Andrew Thompson, Office, 128, Res., 210.	
Granite Falls..	M. S. Nelson, Office, 150-2, Res., 150-3. Paul G. Schmidt, Jr., Office, 17, Res. 219.		Fargo.....	*E. M. Watson, Office, 926-W, Res., 926-R. Geo. V. Ivers, Office, 6377, Res., 6377.	
Montevideo...	§‡L. R. Lima, Jr., Office, 301, Res., 474. Geo. S. Bergh, Asst. Surgeon, Office, 302.		Sisseton.....	John W. Powell, Office, 313, Res., 257. P. D. Peabody, Jr., Office, Tekakwitha Clinic.	
Milan.....	W. A. Owens, Office 301. Res. 818.		Britton.....	Leo. W. Graff, Office, 74., Res., 41.	
Appleton....	M. A. Burns, Office, 32, Res., 30. W. C. Kaufman, Office, 3, Res., 63.			F. D. Gillis, Office, 2020, Res., 2639. ‡Dr. F. D. Gillis, Jr., Office, 2020., Res., 4338.	
Ortonville....	Edward J. Kaufman, Office, 3, Res., 324. *C. Bolsta, Office, 35, Res., 1.		Mitchell.....	W. A. Delaney, Asst., Office, 2067, Res., 2113. O. J. Mabee, Oculist, Office, 2537, Res., 2862. Dr. R. A. Weber, Oculist, Office, 2012, Res., 3993.	
	*B. R. Karn, Office, 35, Res., 65. Jacob F. Karn, Office, 35, Res., 414.		Woonsocket...	Wm. R. J. Kilpatrick, Office, 201, Res., 202.	
Milbank.....	D. M. O'Donnell, Office 35, Res., 33J2. *Walter T. Judge, Office 92, Res. 128. David A. Gregory, Mitchell Bldg., Office 173, Res. 173W2.		Tulare.....	C. A. Seemann, Office, 1403, Res., 1404.	

§Indicates salaried Company surgeons who should be used whenever possible.

‡Indicates surgeons equipped to conduct physical examinations of employees for entrance into service, promotion or re-examination.

*Indicates surgeons equipped to conduct physical examinations of employees for re-examination only.

WATCH INSPECTORS.

Minneapolis... O. J. Quale.	Montevideo. E. B. Sorenson.	Aberdeen... Chas. A. Sauer.	Britton.... Draper Jewelry Co.
Minneapolis. A. Bertas.	Ortonville... F. B. Wickland.	Roscoe.... Agent Roscoe	Mitchell.... Everett Cotton.
Minneapolis. Ben H. Anderson & Co.	Milbank... Jenson & Christenson.	Mobridge... S. A. Amunson.	Linton.... Wm. Heyerman.
Minneapolis. O. P. Gustafson Co.	Andover ... C. B. Summers, Agent.	Farmington. E. M. Gerster.	
Glencoe.... Wm. G. Gould, Inc.		Wheaton.... A. H. Diepenbrock.	

J. G. WIK,
A. E. JERDE,
B. F. FULLER,
L. E. LARSON,
P. W. HALING,
F. K. CRAMER,
F. L. HARVEY,
E. J. ALBRECHT,
R. K. NYSTROM,
W. L. MAYER,
G. L. WEIS,
Train Dispatchers.

W. A. SMITH,
Chief Dispatcher,
First, Second, Fourth,
Fifth, Sixth, Seventh,
and Eighth Subdivisions.

J. J. NENTL,
Trainmaster.

R. D. MATHIS,
Chief Dispatcher,
Third, Ninth, Tenth,
Eleventh and Twelfth
Subdivisions.

SPECIAL INSTRUCTIONS

ALL SUBDIVISIONS

G1 Engineers operating engines equipped with the oscillating emergency red headlight will be governed by the following:

When the air brakes are applied from any cause other than in normal operation by the engineer, or when it is found necessary to stop train due to some defect, or under circumstances which might cause a derailment and the fouling of adjacent main track, engineer must immediately display the oscillating red headlight.

Engineers on approaching trains will take notice and immediately bring train to a stop, and will not proceed until track is found to be safe and clear for their movement.

These instructions are applicable at all times, both day and night. The emergency headlight should not be used for any other purpose.

The operation and use of this device does not in any way relieve trainmen and enginemen from full compliance with Rules 99 and 102.

The following will govern the use and handling of the "Emergency Red Rear End Light" on trains so equipped:

Emergency Red Rear End Lights. Trainmen on trains equipped with oscillating emergency red rear end lights must familiarize themselves with the location of the switches which control the lights and will be governed by the following:

The emergency red rear end light will be used on trains so equipped in the following manner:

To provide protection to trains on adjacent tracks as required by Rule 102.

To provide supplemental protection under Rule 99 in all circumstances where its use is necessary to stop following trains on one or more tracks.

A following train observing this emergency red light displayed must immediately reduce to restricted speed and be governed by instructions of flagman.

The use of this emergency red light does not in any way relieve the flagman from full compliance with Rules 99 and 102.

Portable emergency red lights must be removed before coupling onto the car.

G2 The Mars white light on engines so equipped shall be used at all times between the hours of sunset and sunrise, and during daylight hours on days that are dark, or during sleet, snow, fog or rain, such as would impair the vision of motorists and hinder them from observing approaching trains, except the light must be turned out when moving through certain portions of large terminals and yards where yard engines are employed, approaching junctions, or meeting points, or while standing at those points, and when approaching trains in the opposite direction on double or three or more tracks.

In case of failure of the regular headlight, the Mars white light should be used in stationary position as the headlight.

G3 Where Approach signals are used in connection with fac- ing point switches or manual block signals, the switch or block signal will be considered as the Home signal.

G4 Employes are prohibited from:

Removing any of the appliances of engines or cars that will endanger the safety of themselves or others.

Standing on top of high cars while passing under bridges or through tunnels.

Getting on the end of an engine or of a car as it approaches them.

Going between or running ahead of moving cars to couple, uncouple, open, close, or arrange knuckles of couplers.

Working on the side of cars or trains where there are buildings, sheds, cattle chutes, or other projections.

Kicking or holding drawbar in position to make a coupling with an approaching car or engine.

Following other dangerous practices.

G5 When, for any reason, adjustment is necessary to a drawbar, knuckle pin, or locking block prior to making coupling or when coupling does not make, the engine or cars must be separated not less than 20 feet and action taken to prevent the cars from moving before going between the cars to make the adjustments.

G6 Whenever a car without a drawbar or draft timber is to be moved by a train or engine and it is necessary to chain the car to other cars or engines, employes are prohibited from going between such car and other cars or engines until the persons performing the work have a thorough understanding with the engineer and other members of the train crew. During the process of chaining up the car, the car itself must be properly secured while being chained to other cars, and if the car is to be chained to the engine, then the car must be secured and the brakes on the engine set to avoid a movement of any kind. The engineer must not release the brakes until he has received verbal information that all employes are out from between the cars or engines, and under no circumstances must employes again go between such car or cars and engines until the engineer and other members of the train crew have been notified and the car properly secured and the engine brake set.

G7 Employes must not handle or board cars or engines that bear BAD ORDER cards without first ascertaining the nature of the defect so that they may guard against injury.

G8 When using hand holds and ladder or stirrup steps to descend from engine, car or other equipment, employes must face the equipment and be sure of a secure handhold and footing.

G9 Employes must not step on track rails nor other similar objects when it can be avoided.

G10 When run-ways, gang-planks or skids are used in handling freight to or from cars, they must be secured to prevent slipping.

G11 Lighting enginemen's torches by holding them in the fire box is hazardous and must not be permitted.

G12 Employes are prohibited from riding:

On engine footboards or pilot steps between engine and car when cars are being pushed.

On leading footboard or pilot steps while coupling engine to cars.

On deadwoods, drawbars, brake beams, journal boxes and brake wheels.

On ends of cars containing lading which may shift.

On engine pilot or footboards, sides or ends of cars, while going in or out of depressed tracks.

On forward footboard or pilot steps of engine in direction the engine is moving except in cases where operating conditions make it necessary for safety and then only one employe must ride on the footboard.

In the gangway of engine.

G13 When necessary to go outside when locomotive is either standing or moving, extreme caution must be exercised to avoid slipping or falling from cab ledge (catwalk) or running board. Cab ledge (catwalk) is not to be used on standing locomotives when access to the running board can be had by other means.

G14 The use of gasoline stoves in Railroad Company's equipment or buildings is prohibited; the use of oil stoves other than modern kerosene stoves (preferably those bearing the Underwriter's label) is also prohibited.

This does not apply to U. S. Army Field Ranges when installed under the supervision of a U. S. Army commissioned officer and operated by his men.

G15 The provisions of Rule 815 also apply to transfer movements within yards.

G16 All 44-ton Diesel engines dead in freight trains must be handled at rear of train just ahead of the caboose and when a pusher engine is placed on the rear of the train, the 44-ton Diesel engine must be placed behind the pusher. When there is a 44-ton dead Diesel engine in the rear of the train, the train must not be pushed nor pulled from the rear, and the dead Diesel engine must not be handled in switching movements in conjunction with other cars.

The following equipment must not be towed or operated under its own power through water in excess of the maximum height of water above rail shown below. When towed or operated under own power through water of lesser depth than that shown below, a speed of three miles per hour must not be exceeded.

Diesel power units 600 and 1000 H.P. Switchers, 4½ inches, all other Diesel engines and Gas-Electric Motor cars, 8 inches.

When operating through water under own power, controller should be in Series position.

G17 The following cars, loaded or empty, will be handled next ahead of the caboose giving preference in the order shown, except that at least one car must be handled between a flat car loaded with rails and the caboose:

Bad order cars.

Wood underframe flat cars.

Switch rear "S.R." cars.

G18 Unoccupied outfit cars of steel underframe or steel center sill construction when inspected and passed by a Car Department inspector, may be hauled in any part of the train.

G19 For the comfort of the passengers, the air-conditioning on our air-conditioned passenger trains should be kept operating as long as possible. When approaching stations where cars are to be picked up or set out between the engine and the rear car, the steam line must be blown out at the proper place and the steam shut off before the train stops. At the final terminal of the equipment, when no cars are to be set out between the engine and the rear car, the fireman will simply shut off the steam as soon as the train stops in the station.

G20 In case of heavy rain or violent windstorm, the operator must notify the section foreman.

G21 A yellow flag by day stencilled ELECTRIC CHARGE LINE and in addition, a yellow light by night, placed at one or both ends of a passenger car standing on a yard track, indicates that the battery of the car is connected to a charge line. When thus protected, it must not be coupled to or moved before the charge line has been removed. Other equipment must not be placed on the same track so as to intercept the view of the yellow signals without first notifying the workmen; in the absence of the workmen, the signals may be moved to the end of the equipment so placed to afford the necessary protection.

DEFINITIONS

G22 Centralized Traffic Control.—A block or a series of consecutive blocks, the signals of which, together with certain switches, are controlled from a central location.

Remote Control Interlocking.—A system of operating outlying signal appliances from a designated point.

C.T.C.—Abbreviation for Centralized Traffic Control.

CENTRALIZED TRAFFIC CONTROL

G23 (a) On portions of the railroad so specified in the timetable, trains will be governed by block signals whose indications will supersede the superiority of trains for both opposing and following movement on the same track.

(b) Except as affected by Special Instructions G23 (a), all block signal rules and operating rules remain in force.

(c) The movement of trains and engines will be supervised by the train dispatcher who may also control the C.T.C. When the C.T.C. is controlled by other than the Dispatcher, the Dispatcher will issue the necessary instructions to the operator at the control station, location of control station will be designated by Special Instructions.

(d) Train or engines must not enter C.T.C. territory unless the governing signal displays a Proceed indication or unless authority is obtained from the authorized employee at the control station.

(e) In case of failure of a Stop signal, authority to proceed will be issued orally by the authorized employee at the control station.

(f) Trains or engines must not move beyond the limits of C.T.C. territory without the proper authority including the information required by Rules S-83 and D-83.

(g) When the governing signal displays a Stop indication and the operator knows that the interlocked switches are in proper position and there are no opposing or conflicting train or engine movements involved, he will authorize the train or engine to proceed in the following form:

"You may proceed at restricted speed to the next signal."

If the operator does not positively know that there are no opposing or conflicting train or engine movements involved or that the interlocked switches are in proper position, he will issue authority to proceed in the following form:

"You may proceed under protection of a flagman to the first signal that displays a Proceed indication."

These instructions must be repeated by the conductor or engineer to insure correct understanding.

See Rule 668(A).

(h) When the governing signal displays a Stop indication for an approaching train or engine and the means of communication have failed, the train or engine may proceed at restricted speed, when preceded by a flagman, to the next signal that displays a Proceed indication, or to the next point of communication. Flagman must be sent far enough in advance to insure full protection.

(i) Where main track switches are not interlocked or equipped with electric locks, when a train or engine enters a siding or other track or makes a crossover

movement, the operator in charge must be notified when the movement is complete and the main track switches have been closed and locked. The switches must not be opened nor will the train or engine enter upon or foul the main track without first receiving authority from the operator.

- (j) A train or engine must not move in the opposite direction to that authorized by the governing signal without proper authority from the operator, unless preceded by a flagman sent far enough in advance to insure protection.
- (k) Instructions for the operation of the electric locks on hand operated switches are posted in telephone booths or on the inside of the door of the locks.
- (l) Dual Control switches are located at Interlocking in C.T.C. territory. See Rules 663 (A), 663 (B) and 663 (C).

GENERAL SPEED RESTRICTIONS

G24 When freight cars (except cars that are equipped for passenger train service) are hauled in a passenger train, the maximum speed of that train will be that prescribed for freight trains in that territory unless a different speed is authorized by bulletin or train order.

G25 Diesel or Electric engines with unobstructed view in either direction may be operated at permissible speeds in either direction.

Diesel or Electric engines with restricted view in one direction must, when operated in that direction, reduce speed to the extent necessary for safe operation.

Dead engines must not be hauled in trains without instructions from the chief dispatcher and must be accompanied by a competent rider, except a rider is not required for Gas-Electric or Diesel engines.

Diesel engines moving dead in train will come under the provisions of Rule 806 and when the doors of the locomotive are locked and the hand brake is not accessible, a freight car with operative hand brakes must be coupled to the diesel with uncoupling mechanism made inoperative.

A rider is not required for dead engines handled by yard crews in terminals, except where condition of dead engine or other circumstances may require for safe movement.

Engines with side rods removed from one side only, must not be hauled in trains.

Dead engines equipped with wood underframe tenders, when hauled in trains, should be placed in the rear of the train just ahead of any Switch Rear cars.

G26 Gas-Electric motor cars should not be hauled dead in trains unless disabled. When necessary to haul such cars dead in freight trains, they should be hauled on the rear of short freight trains.

G27 Dead engines must not be hauled backward in trains if it can be prevented and then only at slow speed.

Conductors will notify engineers when one or more dead engines are to be hauled in trains and the conditions under which they are being handled, so that the speed may be regulated accordingly.

G28 When dead engines with side rods disconnected are hauled in trains there must be at least 8 cars between engines so hauled.

G29 Dead engines of Class K type or larger when hauled in trains should be placed approximately 10 cars from the road engine.

G30 Unless otherwise restricted the following equipment must not be moved in excess of the maximum speed shown below and further reduction must be made where conditions require:

Type of equipment	M P H
Trains handling loaded air dump cars (must stop when meeting trains on double track)	25
Work trains with workmen or occupied outfit cars	25
Lidgerwood unloaders	15
Scale Test cars on branch line 20, on main line	25
Class I engines	25
Passenger trains handled or helped by freight engines with single trucks	60
F5 and F6 engines (on divisions or portions of divisions where authorized to be used)	75
K-1 engines on passenger trains (but must not be used except in extreme emergency)	45

L-2 and L-3 engines (on divisions or portions of divisions where authorized to be used)	50
S2 and S3 engines (on divisions or portions of divisions where authorized to be used)	70
Dead engines with side rods disconnected	15
Dead engines with side rods in position	25
Dead engines with all side rods connected, pistons removed and valve motion disconnected	45
Engines with side rods off and main rods connected when working steam, running light or in train	15
Engines (other than Mallet type) with side rods in position and one main rod removed, light or hauling cars	25
Mallet type engines working steam with one main rod removed	20
Diesel switchers, either dead in train or operating under their own power (except 600 HP Alco switchers, 1600 to 1603 inclusive)	45
600 HP Alco switchers, series 1600 to 1603 inclusive	40
All 44-ton Diesel engines:	
When dead in train	25
When under own power	30

G31 Unless otherwise specified, the speed of all trains or engines approaching interlocked railroad crossings must be reduced, and passenger trains must not exceed 45 miles per hour and other trains or engines 25 miles per hour when passing over such crossing. The stated speed must be further reduced where conditions require. This does not apply to railroad crossings protected by automatic signals or gates, trains and engines will approach such crossings at restricted speed and if proper proceed indication is received, may pass over the crossing at the speed prescribed by Special instructions or bulletin.

The speed of all trains must not exceed 20 miles per hour while passing over railroad crossings protected by signals or gates unless otherwise specified.

G32 The speed of trains handled by Gas-Electric or other similar type power, when consisting of power unit only, must not exceed 10 miles per hour when approaching and passing over railroad crossings protected by automatic signals.

G33 That enginemen may have knowledge of the maximum permissible speed around curves and at points where normal authorized speed must be restricted, a yellow sign with the black letters R.S. and black figures and placed at an upward angle of 45° on the right hand side of the track, indicates that the permissible speed beginning 3000 ft. distant corresponds in miles per hour, to the figures shown. A yellow sign with the black letters R.S. and placed in a vertical position on the right hand side of the track, indicates that normal speed may be resumed.

These signs do not apply to trains which by time-table or other instructions, are restricted to a slower speed.

Where these signs have two sets of figures the outside figures apply to the movement of freight trains and those nearest the track apply to passenger trains.

G34 Spring switches:

Movement in facing point direction over a spring switch equipped with facing point lock may be made at normal speed. Movement in facing point direction over a spring switch not equipped with facing point lock must not exceed 25 miles per hour. If switch is lined for turnout, the allowable turnout speed must be observed.

Movement in trailing point direction over a spring switch on track for which the switch is lined may be made at normal speed.

Movement in trailing point direction which springs the switch points must not exceed 40 miles per hour.

If movement is through turnout the allowable turnout speed must be observed.

See Rules 520 to 525 inclusive.

G34(a) Spring switch must not be thrown by hand when wheels are standing on any part of the switch points, nor before the points have completed their full movement after being trailed through.

G35 In addition to Consolidated Code Rule 801 about the handling of occupied outfit cars, the following will also apply on this Railroad:

When occupied outfit cars are set on a siding, the switches at each end should be spiked to prevent any possibility of a train striking the cars.

The same principle will also apply when such cars are placed on other side tracks; but when, for operating reasons, it is not practicable to have the switches spiked, the train dispatcher must be notified.

When occupied outfit cars are standing on other than siding and the switches on each end are not spiked, a yellow signal must be displayed on each end of the outfit cars. Under such conditions, the cars must not be moved except when necessary and then only after the man in charge has given his permission. When other cars are placed on the same track, the yellow signal must be moved to the end of the string of cars on that track where it can be plainly seen.

G36 When a train order office is closed during the period authorized by timetable or bulletin, the light in the train order signal will be extinguished.

G37 Excessive use of sand at any point is prohibited and its use must be restricted to actual necessity.

G38 When passenger trains are unusually delayed passengers should be informed as to cause and extent of delay.

Conductors will make suitable announcements to passengers on trains, or arrange for brakeman and sleeping or parlor car employees to do so.

Agents or station masters will see that such announcements are made to passengers in stations when waiting for trains.

Public address system should be utilized both at stations and on trains when available.

G39 In complying with Rule 3 of the Consolidated Code of Operating Rules and General Instructions, the prescribed form for yardmasters and foremen of yard engines to register the time when watches are compared will be the place provided on back of time slip Form 3256.

G40 When two or more diesel engine units are coupled together the numerals and suffix letter of the leading unit will be illuminated at all times when in service. The numerals and suffix letter of trailing units must not be illuminated.

The number and suffix letter of the leading unit only to be used in train orders.

G41 Where Automatic Block and Interlocking rules and signal indications require movement at RESTRICTED SPEED, such movement must be made prepared to stop short of train, obstruction or switch not properly lined, and be on the lookout for broken rail or anything that may require the speed of a train to be reduced but a speed of 15 miles per hour must not be exceeded.

X1 Trains handling steam derricks must not exceed the following speed limitations. The indicated maximum speeds must be further reduced on tangents and on curves where track is not in proper condition for the specified maximum speeds.

	On Tangent	On Track	On Curves
Between So. Mpls. and St. Louis			
Park	35 M.P.H.	25 M.P.H.	
Between St. Louis Park and M-bridge	40 M.P.H.	25 M.P.H.	
Between Aberdeen and Mitchell	25 M.P.H.	20 M.P.H.	
Between Farmington and Cologne	25 M.P.H.	15 M.P.H.	
Steam derricks that are not restricted may be operated over other subdivisions at not to exceed twenty (20) miles per hour on tangent and ten (10) miles per hour on curves, or at a slower speed if conditions require.			

X1 (A) Steam derrick X18 stationed at Mpls. may be operated on 1st, 2nd, 3rd, 4th and 9th Sub-Divisions only.

X2 Trains handling rotary snow plows, locomotive cranes, Jordan Spreaders, shovels, pile drivers and ditching machines must not exceed speed limitations shown below. The indicated maximum speeds must be further reduced on tangents and curves where track conditions do not justify the specified maximum speeds. Engine and train crews will make frequent observations of how these machines are riding and when in damaged or questionable condition, or when this equipment is hauled in trains with the heavy end trailing, the speed must be further reduced to insure safe moving.

	On Tangent	On Track	On Curves
On First, Second, Third and Ninth Sub-divisions	35 M.P.H.	25 M.P.H.	
Between all other points	20 M.P.H.	15 M.P.H.	
X3 The speed of all trains or engines passing through turnouts must not exceed 13 miles per hour, except those turnouts laid with long frogs and designated by Special instructions or bulletin where the speed may be increased to 25 miles per hour, unless otherwise authorized.			
Turnouts laid with long frogs are located at:			

Station	Location	Permissible Speed
Tower E14	End of Double Track	
	Westward Track	50 M.P.H.
Hazeltine	East End of Siding	25 M.P.H.
Stewart	East End of Siding	25 M.P.H.
Hector	East End of Siding	25 M.P.H.
Bird Island	West End of Siding	25 M.P.H.
Bird Island	West End of Yard Track, #1	25 M.P.H.
Danube	East End of Siding	25 M.P.H.
Sacred Heart	West End of Siding	25 M.P.H.
E118	End of Double Track	
	Westward Track	
	Passenger trains	50 M.P.H.
	Other trains	40 M.P.H.
E122	End of Double Track	
	Westward Track	
	Passenger trains	50 M.P.H.
	Other trains	40 M.P.H.
Rock Cut	End of Double Track	
	Eastward Track	50 M.P.H.
Swift	End of Double Track	
	Westward Track	50 M.P.H.
Milan	East end and west end of siding	25 M.P.M.
Milbank	End of Double Track	
	Eastward Track	35 M.P.H.
Summit	End of Double Track	
	Westward Track	35 M.P.H.
Bristol	End of Double Track	
	Eastward Track	35 M.P.H.
Groton	End of Double Track	
	Westward Track	35 M.P.H.
Bath	End of Double Track	
	Eastward Track	35 M.P.H.

X3 (A) All spring switches except those indicated below are equipped with facing point locks, permitting maximum permissible speed in the territory involved while moving against the points. The speed must not exceed 25 MPH while moving against the points at the following spring switches. (See special instructions G34.)

Aberdeen West End of Double Track.

X4 Five minute fusees should be used in Automatic Block Territory and on fourth, fifth, seventh, eighth, tenth, eleventh and twelfth subdivisions.

X5 The speed of steam engines when running backward, either light or handling train, must not exceed 25 miles per hour on the 1st, 2nd, 3rd and 9th Subdivisions or 15 miles per hour on other subdivisions without instructions from proper authority.

X6 Following is location of emergency connections for taking diesel engine boiler water between Minneapolis and M-bridge:

Glencoe	—Main line west water column.
Bird Island	—At service tank.
Minnesota Falls	—In fire hydrant house north side of track opposite treating plant.
Montevideo	—Both east and west main line water columns.
Milbank	—East bound main line water column.
Summit	—Inside small storm shed at main line water column.
Bristol	—East bound main line water column.
Roscoe	—West bound main line water column.
Mobridge	—Both east and west bound water column pits.

FIRST SUBDIVISION

19

X7 Speed Restrictions (In addition to General Speed Restrictions).

	Passenger Trains	Other Trains
Tower E-14—Westward Track	50	40
Tower E-14—Eastward Track	70	45
Between E118 and E122 and over G. N. crossing at E122		
Trains using westward track through turnouts at each end and over G. N. crossing at E122	50	40
On 6° and 4° curves, east and west of MP 541	40	40
Trains using eastward track and over G. N. crossing at E122	70	50
Norwood M & StL RR crossing	60	45
Minneapolis through switches between 6th Ave. and 8th Ave.	8	8
Minneapolis approaching and passing over employees crossing middle of 8th St. coach yard	10	10
So. Minneapolis over Cedar and Franklin Aves	8	8
So. Minneapolis over Hiawatha Ave.	10	10
So. Minneapolis over Junction Switch	15	15
Between So. Minneapolis and Minneapolis Restrict- ed Speed	Restrict- ed Speed	Restrict- ed Speed
Between So. Minneapolis and St. Louis Park	60	25
St. Louis Park, over Wooddale and Brunswick Avenues	25	25
Hopkins between 7 AM and 5 PM at Thresher works crossings, eastward trains	40	40
Westward trains	25	25
Glencoe over street crossings	25	25
Glencoe—Trains using siding over Greeley Ave.	10	10
Montevideo—2100 ft. east to 1200 ft. west of passenger depot	20	20
Class S2 and S3 engines when running light	45	
G6 Engines when running light	25	

X8 Class S-2 and S-3 engines must not be operated on the following tracks:

Bass Lake	All yard tracks except 16, 17, 18, 19, 20, 21, 22, 23 and 24.
Chanhassen	House track—400' on stub end.
Augusta	House track—500' on stub end.
Cologne	The Farmington Line main tracks east of the second crossing, east of the east yard switch. Old eastward siding—1500' on east end.
	Yard tracks 2 and 3—1500' on east end.
	Yard tracks old 5 and 6—entire length.
	Mill track.
	Wye tracks.
Norwood	Mill track.
Plato	House track—west of derail.
	Mill track—between derails.
Glencoe	All tracks on north side of depot west of depot.
	Tile track.
	Mill track.
Brownston	Middle track.
Hector	Mill track.
Bird Island	Coal dock track from coal hopper east.
Minnesota Falls	House track.
Granite Falls	Siding from depot east.
	Standard Oil spur.
	House track from stockyard east.
Wegdahl	House track from elevator to east derail.
Montevideo	House track west of frt. house.
	Mill spur and all spur tracks leading from same.

Elevator track (Equity).

Old main line.

Sanding track—except 60' from switch.

Roundhouse track No. 6.

Roundhouse coal track.

X9 At Minneapolis the City Ordinance prohibits the sounding of locomotive whistles within the city limits except in case of emergency or in order to prevent accidents.

X10 South Minneapolis is a register station only for trains starting or terminating at that station.

X11 Rules 251, 253 and 254 are in effect on eastward and westward tracks between Tower E-14 and South Minneapolis for movement with the current of traffic.

X12 At Minneapolis, trains or engines moving into the Depot must receive signal from switch tender at Washington Avenue, and after receiving signal to proceed, move at restricted speed.

X13 At South Minneapolis, trains or engines in either direction must approach the crossover at 24th Street prepared to stop and proceed only on signal from switchtender.

X14 All trains or engines in either direction will approach hand throw crossover switches located just east of Cedar Avenue, South Minneapolis, prepared to stop, unless switches are properly lined and signals indicate Proceed.

X15 Freight trains and yard engines will call yardmaster at South Minneapolis from telephone located at Cedar Avenue and get permission from him to proceed.

X16 The movement of passenger trains and passenger equipment backing into the Minneapolis depot must be controlled by trainman handling air from the rear car. A complete stop must be made at Washington Avenue bridge, and proceed only into depot tracks at restricted speed.

X17 Train orders for movements between Minneapolis and St. Louis Park will be issued over the signature of the Superintendent of the H & D division.

X18 Between South Minneapolis and Bass Lake all trains and engines will operate at a reasonable rate of speed over street crossings.

X19 Trains and engines will move on south and east legs of wye at South Minneapolis as defined by Rule 93 of the Consolidated Code of Operating Rules and General Instructions.

X20 At Lake Street crossing between Minnehaha and South Minneapolis, all trains and engines must stop short of the crossing and one member of the crew must walk ahead to the sidewalk and ascertain if the track is clear and that the Griswold signals are in Stop position before giving signal to his crew to proceed over the crossing.

X20 (A) Cars left on No. 1 track at Cologne must not be left closer than 250 feet east of Adams Street crossing. Cars left on tracks south of No. 1 track must not be left closer than 65 feet from the east edge of the Adams Street crossing.

X21 C.T.C. Operation on first subdivision is controlled by train dispatcher at Montevideo.

Special Instructions G23 in conjunction with the rules of the Consolidated Code of Operating Rules and General Instructions will govern the movement of trains or engines within this territory.

X22 At Glencoe trains using siding must not exceed 10 mph over Greeley Ave. crossing east of depot.

X22 (A) Extra trains may be run between Glencoe and Montevideo without train orders when CTC operation is in use.

X22 (B) At Tower E14 a light will not be displayed on train order signal until Interlocking route is lined for movement of a train.

X23 In automatic block signal territory Manual Block System Rules will apply when trains are run against the current of traffic.

X24 At Plato, Granite Falls, and Wegdahl, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

X25 A 50-mile-per-hour reduce speed sign is located about 4500 feet west of MP 538 on the single track for westward trains and this sign covers movement over the westward track only. A 50-mile-per-hour reduce speed sign is located about 3000 feet west of E122 and this sign for eastward operation covers movement over the westward track only.

SECOND SUBDIVISION

	Speed Restrictions (In addition to General Speed Restrictions).	
	Passenger Trains	Other Trains
Montevideo—2100 ft. east to 1200 ft. west of passenger depot	20	20
Appleton—GN RR crossing	70	55
From 1000 feet west of MP 573 between Milan and Appleton to 200 feet west of MP 594 between Odessa and Ortonville	70	
Milbank—over Main St. crossing	40	40
From Summit to Twin Brooks, eastward trains	70	45
Webster over street crossings	35	35
On curves from 4 1/2 miles west of Bristol to mileboard east of Andover on westward track	55	45
Groton C & NW RR crossing	70	55
Aberdeen C & NW & G N crossings	20	20
Aberdeen over Main Street and Kline street crossings	10	10
Class S2 and S3 engines when running light	45	
G6 Engines when running light	25	

X27 Class S2 and S3 engines must not be operated on the following tracks:

Montevideo	(See Special Instructions X8).
Watson	Canton Yard spur—except 60' west end.
Appleton	Gravel loading track north of Hiway 7. Storage track except from switch to 1000' east.
Ortonville	Lake track—from bridge to west end. Big Stone spur from Minnesota River bridge to end. All wye tracks. Doubling track.
Milbank	All engine house tracks. Coal shed unloading track from shed east. Boiler house and derrick tracks. Stockyard track from stock chute to west end.
Twin Brooks	House track.
Marvin	House track.
Ortley	Elevator spur. House track.
Waubay	Gravel pit track from switch at house track.
Webster	Auxiliary track.
Holmquist	House track.
Bristol	Engine house tracks. H & D Storage tracks.
Andover	West end house track to stockyard. Engine house lead and all branch line tracks. East leg of wye.
Groton	House track from east switch to depot.
James	House track.
Aberdeen	West yard track No. 10 east end and Nos. 11, 12, 13, 14, 17, 18 and 19. All industry tracks except pocket on City track. All freight house tracks. All repair tracks except wheel pit track and No. 1. Coal storage tracks. Cinder track. 7 wheel storage tracks. South lead to roundhouse off Mitchell Line. Boiler house track. Northwestern Public Service Co. tracks. Supply yard tracks. Coach yard tracks. Ice House west end. C&NW transfer. GN transfer.

X28 Extra trains may be run between Montevideo and Milbank without train orders when CTC operation is in use.

X29 Eastward freight trains of 4000 tons or more will stop at Marvin for inspection and to permit wheels to cool.

X30 At Odessa, engines must not be permitted more than 250 feet beyond the south switch of siding on Cold Spring spur.

X31 At Groton, the normal position of the electrically locked crossing gates is against trains on the C&NW.

X32 A check of the Train Register at the following stations will suffice when passing from double track to single track at points named.

At Milbank—for westward trains entering single track at Summit and Groton.

At Aberdeen and Aberdeen Yard—for eastward trains entering single track at Bath and Bristol.

When opposing trains are due after the registers at the designated stations have been checked, Rule S-83 will govern.

X33 In automatic block signal territory Manual Block System Rules will apply when trains are run against the current of traffic.

X34 At Groton, James, and Bath, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

X35 C. T. C. Operation on second subdivision is controlled by train dispatcher at Montevideo.
Special Instructions G23 in conjunction with the rules of the Consolidated Code of Operating Rules and General Instructions will govern the movement of trains or engines within this territory.

THIRD SUBDIVISION

X36 Speed Restrictions (in addition to General Speed Restrictions).

	Passenger Trains	Other Trains
Between west end of double track at Aberdeen and a point approximately 600 ft. west of Aberdeen yard office	20	20
Roscoe over Highway crossing just east of depot, trains other than No. 15 and 16	20	20
Between Java and Java Junction	12	12
Mobridge when passing passenger station	6	6
Mobridge between 2100 ft. east and 2000 ft. west of depot	20	20
Class S2 and S3 engines when running light	45	
G6 engines when running light	25	

X37 Class S2 and S3 engines must not be operated on the following tracks:

Aberdeen	(See Special Instructions X27).
Roscoe	Roundhouse tracks.
Bowdle	Mill track.
Bowdle Gravel Pit	Wye tracks.
Java	House track.

X37(A) Extra trains may be run between Aberdeen and Mobridge without train orders when the provisions of Rules 261, 263 and 264 are in effect.

X38 At Roscoe, an auxiliary siding 80 cars capacity is located north of main track. Rule 5 applies to the siding south of the main track and west of depot.

X38(A) (a) Between Aberdeen and east end of Mobridge Yard the signals and interlocked switches are controlled by the train dispatcher at Aberdeen. The Westward Stop signal at east end of Mobridge Yard is controlled by the dispatcher at Mobridge.

(b) Trains or engines must not enter this territory without proper signal indication or permission of the dispatcher.

(c) In case of failure of Stop signal authority for a train or engine to proceed will be issued orally by the dispatcher.

(d) When the governing signal displays a Stop indication and the dispatcher knows that the interlocked switches are in proper position and there are no opposing or conflicting train or engine movements involved, he will authorize the train or engine to proceed in the following form: "You may proceed at restricted speed to the next signal."

If the dispatcher does not positively know that there are no opposing or conflicting train or engine movements involved or that the interlocked switches are in proper position, he will issue authority to proceed in the following form: "You may proceed under protection of a flagman to the next signal that displays a Proceed indication."

These instructions must be repeated by the Conductor or Engineer to insure correct understanding.

See Rule 663(A).

(e) When the governing signal displays a Stop indication for an approaching train or engine and the means of communication have failed, the train or engine may proceed at restricted speed when preceded by a flagman to the next signal that displays a Proceed indication, or to the next point of communication. Flagman must be sent far enough in advance to insure full protection.

(f) Trains or engines must not move in the opposite direction to that authorized by the governing signal without proper authority from the dispatcher unless preceded by a flagman sent far enough in advance to insure full protection.

(g) Trains or engines must not enter or foul main track or re-enter main track after having cleared it unless the governing signal displays a proceed indication or unless authority is obtained from the dispatcher.

Where main track switches are not interlocked or governed by signal indications, trains or engines must report to the dispatcher when clear of the main track and switches properly lined and locked.

(h) Trains or engines must not pass beyond the limits of this territory without proper authority including the information required by Rule S-83 or D-83.

FOURTH SUBDIVISION

X39 At Shakopee, crews switching Rahr Malting Plant will not move engines over pit on barley track nor over scale on malt track due to reduced clearances.

X40 At Shakopee, the normal position of the electrically locked crossing gates is against movements on the CMStP&P. At Chaska, the normal position of the electrically locked crossing gates is against movements on the CMStP&P. At Lakeville, the normal position of the electrically locked crossing gates is against movements on the CMStP&P.

X41 At Prior Lake, Shakopee and Chaska, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

X42 At Prior Lake all trains will stop before passing over crossing 100 ft. west of depot.

X42(A) Cars left on No. 1 track at Cologne must not be left closer than 250 feet east of Adams Street crossing. Cars left on tracks south of No. 1 track must not be left closer than 65 feet from the east edge of the Adams Street crossing.

FIFTH SUBDIVISION

X43 At Biscay, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on this siding.

SIXTH SUBDIVISION

X44 Speed Restrictions (in addition to General Speed Restrictions).

	Passenger Trains	Other Trains
Wahpeton over street crossings	25	25
Wahpeton GN crossing	18	18
Fargo between and over both N. P. crossings	10	10

X45 Class L-2 engines may be used on sixth subdivision from Ortonville to four miles west of Ortonville at maximum speed of 20 miles per hour.

X46 At Ortonville, all eastward trains on 6th subdivision will stop before passing over school house crossing.

X47 At Wahpeton, the normal position of the electrically locked crossing gates is against movements on the CMStP&P.

X48 At Fargo, all movements over 18th street must be made under flag protection: Cars must not be dropped or kicked over this crossing.

X49 At Clinton, Graceville, Dumont, Wheaton, White Rock, Fairmount, Tyler, Wahpeton, Abercrombie, Christine, Hickson and Wild Rice, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

SEVENTH SUBDIVISION

X50 At Corona, Wilmot and Peever, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

EIGHTH SUBDIVISION

X51 At Pierpont, Langford, Spain, Britton and Newark, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

NINTH SUBDIVISION

X52 Speed Restrictions (in addition to General Speed Restrictions).

	Passenger Trains	Other Trains
Aberdeen over 3rd Ave. and 6th Ave.	6	6
Aberdeen M & StL crossing		
1 mile East on 9th Subdivision	10	10
Aberdeen C & NW crossing 3.0 miles		
East on 9th Subdivision	20	20
Redfield C & NW crossing 0.2 miles East	20	20
Redfield C & NW crossing 2.2 miles East	20	20
Wolsey C & NW crossing	20	20
Woonsocket over street crossings	10	10
Mitchell over Sanborn street crossing	6	6

X53 At Aberdeen, the normal position of the crossing gates at M&StL crossing one mile east on ninth subdivision is against movements on the M&StL.

X54 At Woonsocket, cars must not be kicked or dropped over the street crossings.

X55 At Loomis, Cuthbert, Spotswood, Ashton, Gallup and Duxbury, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

TENTH SUBDIVISION

X56 At Gage, Westport, Barnard, Frederick, Winship, Ellendale, Duane, Monango, and Potts, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.

ELEVENTH SUBDIVISION

X57 At Loyalton, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on this siding.

TWELFTH SUBDIVISION

X58 At Hosmer, Hillsview, Eureka, Greenway, Zeeland, Hague, Strasburg, and Linton, the siding is also used as a house track; the train dispatcher need not be notified when cars are left on any of these sidings.